

# CAPRANO TDI 15W-40



Mineral lubricant for fast-running Diesel engine used in navigation.

## **SPECIFICATIONS AND APPROVALS**

International specifications	ACEA E7/E5	API CI-4 / CH-4 / SL	
Manufacturers' approvals	Meets the	e requirements of	
Engine	✓ C	aterpillar ECF-2	
✓ Baudouin Performance B	✓ FI	PT-Iveco T2 E7	
✓ Cummins CES 20078/20077/	20076		
✓ MAN M3275	Suitable 1	for the following engines	
✓ MTU Category 2	MITSUBIS	HI (medium speed)	
✓ Volvo VDS-3		` <i>'</i>	
Reduction drive/Reversing gear			
✓ ZF TE-ML 04C			

#### **APPLICATIONS**

TOTAL CAPRANO TDI 15W-40 is suitable for **fast-running Diesel engines** used in **navigation**, especially recent technologies with exhaust gas recirculation, that meet **European standard Stage IIIA** and **American standard EPA Tier 3**.

TOTAL CAPRANO TDI 15W-40 is also adapted to auxiliary systems and transmissions.

## PERFORMANCES AND CUSTOMER BENEFITS

TOTAL CAPRANO TDI 15W-40 contains excellent **viscosity stability in service**, guaranteeing effective engine lubrication in severe conditions.

Outstanding detergent, dispersant and anti-wear properties keep the engine clean and enable effective control of soot, sludge and piston deposits.

Excellent piston cleanliness performance affords effective protection against cylinder liner polishing.

Its anti-wear and anti-corrosion additives ensure longer engine and transmission durability.

## PHYSICAL AND CHEMICAL CHARACTERISTICS\*

TOTAL CAPRANO TDI 15W-40		Method	Value
Density at 15 °C	kg/m <sup>3</sup>	ASTM D1298	889
Kinematic Viscosity at 40 °C	mm²/s	ASTM D445	100
Kinematic Viscosity at 100 °C	mm²/s	ASTM D445	14
Viscosity Index	-	ASTM D2270	140
Pour point	°C	ASTM D97	-30
T.B.N	mgKOH/g	ASTM D2896	11
Sulphated Ash	% m/m	ASTM D874	1.45

<sup>\*</sup> The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

