



# DYNATRANS FR



**TOTAL**

Lubricant for **transmissions** equipped with **wet disk brakes** and **hydraulic systems** for **public works** and **handling equipment**.

## SPECIFICATIONS

International specifications	API GL-4
<b>Meets the requirements of</b> <ul style="list-style-type: none"><li>✓ Renault Agriculture 180596-88.3</li><li>✓ Massey-Ferguson CMS M 1141/1135</li><li>✓ New-Holland NH 420A</li><li>✓ Ford M2C 86B/86C</li></ul>	<b>Suitable for transmission systems</b> FIAT, JCB, KOMATSU, MANITOU

## APPLICATIONS

TOTAL DYNATRANS FR is dedicated to the lubrication of **mechanical transmissions** requiring an **API GL-4** product with **SAE 80W** viscosity.

This lubricant is suitable for:

- Hydraulic lift, servo, transmission and steering systems
- Power-take-offs
- Driving axles equipped with wet brakes

## PERFORMANCES AND CUSTOMER BENEFITS

- Suitable for a wide range of agricultural machinery and public works equipment
- Simplifies maintenance management
- Used in heavy work conditions or in case of vibration phenomena during braking

## PHYSICAL AND CHEMICAL CHARACTERISTICS\*

TOTAL DYNATRANS FR		Method	Value
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	84
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	10.5
Viscosity Index	-	ASTM D2270	108
Pour Point	°C	ASTM D97	-27

\* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

### TOTAL LUBRIFIANTS

562, avenue du Parc de l'Île  
92029 Nanterre cedex  
FRANCE

### TOTAL DYNATRANS FR

Update 12/2014

[www.lubricants.total.com](http://www.lubricants.total.com)



This lubricant does not cause adverse health effects when used in the intended application.  
A safety datasheet is accessible on request from your local dealer or on the website [www.quickfds.com](http://www.quickfds.com)