



TRACTAGRI HDM 15W-40



Lubricant for *naturally-aspirated* or *turbocharged* engines used in tractors and **agricultural machines**.

SPECIFICATIONS AND APPROVALS

International specifications	ACEA E2/E1	API CF-4/SF
Meets the former classifications <ul style="list-style-type: none">✓ MIL. L. 2104E✓ CCMC D4/PD2		Suitable for the following engines DEUTZ, DEERE, FORD, IVECO, NWM, PERKINS...

APPLICATIONS

TOTAL TRACTAGRI HDM 15W-40 is recommended for **agricultural Diesel engines**, especially technologies without pollution control.

This lubricant is adapted to **naturally-aspirated or turbocharged Diesel engines**, and also service vehicle **gasoline engines**.

TOTAL TRACTAGRI HDM 15W-40 is suitable for every tractors or agricultural equipments used in **soft conditions**.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL TRACTAGRI HDM 15W-40 contains **viscosity stability** in service.

This lubricant exhibits **thermal stability** and **oxidation resistance**, ensuring proper engine lubrication.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL TRACTAGRI HDM 15W-40		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	888
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	110
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	13.8
Viscosity Index	-	ASTM D2270	125
Pour Point	°C	ASTM D97	-27
T.B.N	mgKOH/g	ASTM D2896	12

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS
562, avenue du Parc de l'Île
92029 Nanterre cedex
FRANCE

TOTAL TRACTAGRI HDM 15W-40

Update 07/2014

www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com