



A brand of **TOTAL**

EVOLUTION 900 FT 5W-40



Very high performance lubricant using ELF synthetics technology. Intended for lubricating passenger cars Gasoline and Diesel engines.

APPLICATIONS

- Most recent technology engines**
 - Suitable for all gasoline and diesel engines, particularly for most recent ones.
- The most severe journeys**
 - Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions.
- « Vigorous » driving, all times of year**
 - For all driving styles, particularly « vigorous » and high speeds.
 - Meets the needs of the motor manufacturers regarding extended oil change intervals.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

International specifications	ACEA : A3/B4 API: SN/CF	
OEMs approvals	VOLKSWAGEN PORSCHE BMW MERCEDES BENZ RENAULT	VW 502.00 / 505.00 A40 BMW LL-01 MB-Approval 229.5 (backward compatible MB-Approval 229.3) MB-Approval 226.5 RN0700/RN0710
	Meets the requirements of: FIAT 9.55535-M2 / CHRYSLER MS-12991	

CUSTOMER BENEFITS

- Optimal performance**
 - Excellent engine protection, particularly against timing system wear.
- Excellent engine cleanliness and protection**
 - Ensures maximum engine cleanliness.
- Lengthens engine life**
 - Outstanding thermal stability, oxidation resistance eliminating any degradation even in very severe use.
- Facilitates cold starts**
 - Immediate lubrication of engine parts during cold starts, leading to longer engine life.
- Extended oil change intervals**
 - Meets the requirements of the manufacturers as regards extended oil change intervals.

CHARACTERISTICS

	Method	Units	SAE Grade 5W-40
Viscosity at 40°C	ASTM D445	mm ² /s	90
Viscosity at 100°C	ASTM D445	mm ² /s	14,7
Viscosity index	ASTM D2270	-	172
Pour point	ASTM D97	°C	- 42
Flash point	ASTM D92	°C	230
B.N.	ASTM D2896	mgKOH/g	10

The typical characteristics mentioned represent mean values