



A brand of **TOTAL**

# EVOLUTION 900 FT 0W-30



**100% synthetic and very high performance lubricant based on ELF technology. Intended for lubricating passenger cars Gasoline and Diesel engines.**



## APPLICATIONS

**Most recent technology engines**

- Can be used for all Gasoline and Diesel engines, especially for the most recent engines. The vehicle owner manual should be checked before using.

**The most severe journeys**

- Satisfy the most difficult using conditions (city, road, motorway).

**« Vigorous » driving, all times of year**

- Is appropriated for all driving types, in particular for sporting or intense drive and for every season.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

## PERFORMANCES

**International specifications**

ACEA : A3/B4  
API: SL/CF

**OEMs approvals**

VOLKSVAGEN VW 502.00 / 505.00  
RENAULT RN0700 / RN0710  
MERCEDES BENZ MB-Approval 229.5 (backward compatible MB-Approval 229.3)  
MB-Approval 226.5  
FORD FORD WSS-M2C937-A

## CUSTOMER BENEFITS

**Anti-wear protection**

- Ensures outstanding engine longevity.

**Oxidation resistance**

- Provides for extra long intervals between oil changes.

**Engine cleanliness**

- Develops performance and power.

**Suitable for low and high temperatures**

- Facilitates ignition in very cold weather and maintains protection of the parts even in great heat.

**Fluidity**

- Reduces friction and therefore creates fuel savings, which decrease CO2 emissions.

## CHARACTERISTICS

	Method	Units	SAE Grade 0W-30
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	68,45
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	12,18
Viscosity index	ASTM D2270	-	170
Pour point	ASTM D97	°C	- 45
Flash point	ASTM D92	°C	226
B.N.	ASTM D2896	mgKOH/g	10.4

The typical characteristics mentioned represent mean values