



# ELF MOTO<sup>4</sup> ROAD 10W-40

4-stroke motor oil

## KEY DATA

- MOTORCYCLE RANGE



- 4-STROKE MOTOR OIL
- SYNTHETIC BASED
- SAE 10W-40

- INTERNATIONAL STANDARDS

- ✓ API SL
- ✓ JASO MA2

- LEVEL



## APPLICATIONS

ELF MOTO<sup>4</sup> ROAD 10W-40 is a lubricant that is particularly recommended for all types of 4-stroke engine motorcycles, in compliance with the API SL and JASO MA2 international standards.

ELF MOTO<sup>4</sup> ROAD 10W-40 is perfectly compatible with catalytic converters. The oil-change intervals recommended by the constructors and the minimum required viscosities must be complied with. This lubricant is compatible with lead-free fuels. This multi-purpose lubricant meets the severe requirements of urban traffic and long-distance runs.

ELF MOTO<sup>4</sup> ROAD 10W-40 is fortified with synthetic based oils, providing hydrodynamic lubrication and superior engine cleanliness.

ELF MOTO<sup>4</sup> ROAD 10W-40 has a specific reactivity to temperature variations. Its maximum fluidity at low temperatures improves injection and ensures that oil pressures rise quickly.

## CUSTOMER BENEFITS

- Viscosity controlled in relation to temperature:** ELF MOTO<sup>4</sup> ROAD 10W-40's additives thicken the oil at high temperatures and give it fluidity at low temperatures. The correct oil film is obtained by controlling the viscosity in accordance with temperature using Viscosity Index Improvers. ELF MOTO<sup>4</sup> ROAD 10W-40 viscosity incorporates superior lubrication performance, ensuring easy cold start-ups, fast oil pressure rises and low friction between moving engine components.
- Piston ring sealing, power gains:** ELF MOTO<sup>4</sup> ROAD 10W-40 reduces piston ring groove fouling for optimum sealing during combustion. This ensures that the engine retains its full power.
- Oxidation resistance:** ELF MOTO<sup>4</sup> ROAD 10W-40 has anti-oxidant additives which neutralise and slow down the oxidation process. This prolongs the lubricant's lifetime and keeps the oil fluid and efficient. It remains homogenous and its acidity level scarcely changes.
- Anti-clutch slippage, disk protection:** Because of their molecular structure, the base oils are able to form a homogenous film between the clutch disks. The friction factor is adapted to mechanical requirements, preventing clutch slippage and premature disk wear.



## CHARACTERISTICS\*

Test	Unit	Result
Viscosity grade	-	10W-40
Density at 15°C	kg/m <sup>3</sup>	874
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	97.1
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	14.6
Viscosity index	-	156
Pour Point	°C	-33
OC Flash Point	°C	230

\*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## RECOMMENDATIONS FOR USE

Before using the product, the vehicle's user guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at [www.quickfds.com](http://www.quickfds.com).

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

TOTAL Lubrifiants  
Immeuble Le Spazio  
562, avenue du Parc de l'île  
92029 Nanterre Cedex  
France

Last update of this datasheet: 05/2017

# ELF MOTO<sup>4</sup> ROAD 10W-40



Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at [www.lubrifiants.total.fr](http://www.lubrifiants.total.fr).