

Lubricants – Transmission Oils – Automotive

Version: 253/03a

Valvoline[™] Heavy Duty Axle Oil Pro 75W-140

Full synthetic axle oil for axles of trucks and buses.

EP axle oil is suitable for differentials where the manufacturer specifies GL-5 75W-140 lubricant.

Valvoline Heavy Duty Axle Oil Pro 75W-140 is specially developed for severe operating environments in today's heavy-duty drive axles.

O.E.M. approvals

Scania STO 1:0 & STO 2:0A
ZF TE-ML 05A, 12N, 16F, 19C, 21A (ZF001874)

Performance levels

API: GL-5, MT-1
Arvin Meritor 076-M
Mack GO-J

Features & Benefits

Superior protection

Superior protection against wear and tear, also under high stress working conditions.

Advanced additives

Modern additives protect against corrosion, oxidation, foaming and deposits.

Breakdown resistance

Premium synthetic base oils with balanced additive system avoid breakdowns and stick-slip even between extended drains.

Consistent, stable viscosity

Excellent viscosity-temperature properties even at very low temperatures. Highly stable viscosity with long-term multigrade advantages.

Limited Slip properties

Not recommended for limited slip axles.

Applications

Suitable for differentials of trucks and buses where the manufacturer recommends GL-5 transmission oil with a viscosity of SAE 75W-140.

Also used in earthmoving machines and materials handling equipment.

Consistent, stable viscosity

Excellent viscosity-temperature properties even at very low temperatures. Highly stable viscosity with long-term multigrade advantages.

Limited Slip properties

Not recommended for limited slip axles.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline Heavy Duty Axle Oil Pro	
SAE Viscosity Grade	75W-140
Viscosity, mm ² /s @ 100 °C. ASTM D-445	25,5
Viscosity, mm ² /s @ 100 °C. After shearing (CEC: L-45-T-93).	Stay-in-grade
Viscosity, mm ² /s @ 40 °C. ASTM D-445	188
Viscosity Index ASTM D-2270	169
Viscosity, mPa.s -40°C. ASTM D-5293	<150.000
Pour Point, °C ASTM D-5950	-42
Specific Gravity @ 15.6°C. ASTM D-4052	0,859
Flash Point, COC, °C. ASTM D-92	226

**This information only applies to products manufactured in the following location(s):
Europe**

™ Trademark of Valvoline, registered in various countries © 2016

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 253/02a