

# Eni i-Ride scooter 10W-40



## APPLICATIONS

**Eni i-Ride scooter 10W-40** is a synthetic technology lubricant designed to lubricate 4-stroke engines fitted in scooters. Its formulation makes it suitable for use in engines cooled either with coolant or air.

## CUSTOMER ADVANTAGES

- The excellent features of this product make it suitable for use in the most stressed motors, also equipped with Start & Stop systems.
- The special formulation of **Eni i-Ride scooter 10W-40** is able to ensure, due to the excellent lubrication, the best engine protection in all operating conditions, even the most extreme ones.
- The formulation of **Eni i-Ride scooter 10W-40** is developed to perform an effective control of deposits formation.
- The components present in the formulation have been carefully selected to maintain their properties even under operating conditions characterized by high temperatures.

## SPECIFICATIONS - APPROVALS

- API SJ
- JASO MA, MA2



# Eni i-Ride scooter 10W-40



## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	867
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	14.9
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	99
Viscosity Index	ASTM D 2270	-	156
Viscosity at -25°C	ASTM D 5293	mPa·s	6800
Flash point (COC)	ASTM D 92	°C	220
Pour point	ASTM D 97	°C	-24

