

Eni i-Sint tech G 5W-30



APPLICATIONS

Eni i-Sint tech G 5W-30 is a synthetic technology formula designed and manufactured to meet lubrication requirements for GM engines, requiring lubricants with long replacement intervals (LL - Long Life) in accordance with the specifications: GM-LL-A-025 or GM-LL-B-025.

CUSTOMER ADVANTAGES

- The formulation of **Eni i-Sint tech G 5W-30** is developed to ensure excellent performance in any engine operating condition.
- The product provides protection of the mechanical components of the engine against wear and formation of deposits.
- The performance of **Eni i-Sint tech G 5W-30** allows long time use at high temperatures, minimizing degradation due to thermo-oxidative phenomena.
- The product is characterized by excellent fluidity at low ambient temperatures, which makes it easier to start-up the engine under such conditions.
- **Eni i-Sint tech G 5W-30** is suitable for the lubrication of gasoline or diesel engines of cars or light duty commercial vehicles.

SPECIFICATIONS - APPROVALS

- API SL/CF
- GM LL-A-025, LL-B-025



Eni i-Sint tech G 5W-30



CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	859
Viscosity at 100°C	ASTM D 445	mm ² /s	11.9
Viscosity at 40°C	ASTM D 445	mm ² /s	70
Viscosity Index	ASTM D 2270	-	166
Viscosity at -30°C	ASTM D 5293	mPa·s	6400
Flash point (COC)	ASTM D 92	°C	227
Pour point	ASTM D 97	°C	-39
B. N.	ASTM D 2896	mg KOH/g	10.5

