

CARTAGO CAJAS FE LD 75W80



TRANSMISSIONS AND GEARBOXES

Lubricants

Description

Synthetic lubricant for manual gearboxes. This oil has been specially designed to meet the lubrication requirements laid down by the principal vehicle manufacturers for their manual gearboxes. This product is a high performance lubricant that contributes to fuel savings and enables extended change intervals.

Properties

- Excellent protection against gear and synchroniser wear.
- Long life oil that enables extended drainage intervals of up to 300,000 km.
- It has high loading capacity, minimises losses due to friction and provides maximum efficiency.
- It provides smooth driving when changing gear, and extreme operating temperatures of up to -40° C, thanks to its excellent fluidity at low temperatures.

Quality Levels

- API GL-4
- ZF TE-ML 01L/02L/08/16K
- MAN 341 Z-4 /341 E-3
- Eaton Europe
- VOLVO 97305
- DAF Transmissions
- IVECO Transmissions
- RENAULT (B0032/2 Annex 3)

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/mL	ASTM D 4052	0.857
Viscosity at 100 °C	cSt	ASTM D 445	9.6
Viscosity at 40 °C	cSt	ASTM D 445	55
Viscosity at -40 °C	cP	ASTM D 2983	<150.000
Viscosity index	-	ASTM D 2270	150
Flash point, open cup	°C	ASTM D 92	230
Pour point	°C	ASTM D 97	-42

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 5. May 2014.