

# UTTO SUPER THF

AGRICULTURAL



## Lubricants

### Description

State of the art multifunctional lubricant oil (U.T.T.O) for the lubrication of KUBOTA agricultural machinery, transmissions, gearboxes, differential conic assemblies, power take-offs, hydraulic systems, wet brakes (sintered or compound) and clutches. It improves the performance of transmissions and its use is compulsory for vehicles carrying Powershift transmissions; including but not limited to M40, M120, M125X, M128X, M130X and HSTBX2200, BX2350, B3030H, L4100HST, STA35, STV40.

### Properties

- Its formula has been tested under extreme working conditions in compliance with Super UDT fluids' strict requirements stipulated by KUBOTA.
- It improves friction stability and makes clutch operation more comfortable, while maintaining its output power and extending clutch life.
- The tests carried out proved the elimination of brake noises even under extreme conditions of water-contaminated oil.
- Its excellent viscosimetric performance at low temperatures provides maximum protection of the gears when operating under low temperatures.
- It improves the short term performance of transmissions in terms of the sense of comfort while in the long term the useful life of several mechanisms is prolonged.
- Not for use as an engine oil.

### Quality levels

- GL-4
- KUBOTA SUPER UDT
- KUBOTA UDT

### Technical specifications

	UNIT	METHOD	VALUE
Density at 15° C	g/ml	ASTM D 4052	0.873
Viscosity at 100 °C	cSt	ASTM D 445	8.7
Viscosity at 40° C	cSt	ASTM D 445	42
Viscosity index	-	ASTM D 2270	185 min
Flash point, open cup	°C	ASTM D 92	200 min
Pour point	°C	ASTM D 97	-40

*The above mentioned characteristics are typical values and should not be considered product specifications.*

A safety data sheet is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 1. September 2018.