

Description

Products from the DESMOLDOIL range are compounds formulated to act as mould-release agents in various applications. They are made up of a selected blend of bases. More specifically, part of the DESMOLDOIL R base is regenerated, contributing to the recycling of these products as well as fulfilling the technical requirements for the mould release of concrete elements.

The DESMOLDOIL product range has been carefully assessed to ensure compliance with our clients' requirements, in any kind of application and finish (concrete parts, shuttering, etc.) or for any kind of mould with wooden, iron soft-metal, or other surfaces.

Properties

- Good oxidation resistance and storage stability.
- Excellent mould release properties.
- Environmentally friendly (can not be labelled).
- Exceptional coverage.
- Excellent finish.

Technical specifications

	UNIT	METHOD	VALUE
ASTM colour		ASTM D 1500	1.5
Density	g/cm ³	ASTM 4052	0.853
Viscosity at 40 °C	cSt	ASTM D 445	24
Viscosity at 100 °C	cSt	ASTM D 445	4.7
Viscosity Index	-	ASTM D 2270	100
Flash point	°C	ASTM D 92	220
Pour point	°C	ASTM D 97	-18

Unless otherwise indicated, the values stated in the technical characteristics are not specifications and should only be considered as typical.

A safety data sheet is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 1. October 2013.