





Bag filter housing

STAINLESS STEEL SS 316 BAG FILTER HOUSINGS

FILTRO FBA



FEATURES

Model	FILTRO FBA
Material	SS 316
In/Out	DN 80 FLANGE ANSI

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	12 bar

Max working temperature	80°C
Life test	100.000 cycles from 0 to 8 bar

BAGS

1
07 Diam. 7" (175/180 mm)
17" (430 mm) - 32" (810 mm)
161 mm / 166 mm
180 mm





RING TYPE

SI7 Internal ring	175/180 mm
SW7 Welded ring	175/180 mm

APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	In/Out	Bag's end cap	Quantity box	-
FBA316070117300FAM	FILTRO FBA 1x17"	DN80 FLANGE ANSI Blasted	DN 80 FLANGE ANSI	07	1	
FBA316070132300FAM	FILTRO FBA 1x32"	DN80 FLANGE ANSI Blasted	DN 80 FLANGE ANSI	07	1	







Bag filter housing

STAINLESS STEEL SS 316 BAG FILTER HOUSINGS

FILTRO FBA

HOUSINGS CODE LIST Model Material N° bags Bags height Specs and finishing Ring diameter 17" (430 mm) 32" (810 mm) AISI 316 07 Diam. 7" DN80 FLANGE ANSI B3 FBA 316 07 01 17 (175/180 mm) 32 asted 300FAM



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure

Link to product's details pictures, installation pictures

http://www.everblue.it/OtherInstallPics/INS FILTROFBA-01.PDF



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014.

These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS ARTICLES: 4.1 LETTER (a) (ii)

Design code: EN 13445 - 3