



GREASE 100

All purpose Grease

Lithium

NLGI 2

TYPE OF USE

Grease for roller bearings under normal duty conditions, articulations, bearings, hubs, ball joint, cables...

Car, Motorbike, Marine, Transport, Civil engineering machinery, Industry and Farm machines...

For more severe applications such as heavy loads, resistance to water, we recommend using well-adapted products such as TECH GREASE 300, TP/AGRI or MOLYBDEN.

Temperature for use : from -30°C / -22°F to +120°C / +248°F.

PERFORMANCE

Grease with lithium soap and anti-wear, anti-oxidation & anti-corrosion additivation.

Good mechanical stability.

Adequate pumpability at cold temperature.

Anti-corrosion and anti-rust protection.

Adherent.

Designation DIN 51502 : KP 2 K-30

PROPERTIES

Color	Visual	Blue
Consistency grade	DIN 51 818	NLGI 2
Soap		Lithium
Penetrability - 60 cycles	ASTM D217	265 / 295 x10 ⁻¹ mm
Drop point	ASTM D2265	180°C / 356°F
Anti-corrosion EMCOR	IP 220	0 / 0
FAG FE-9 Test	DIN 51 821	F50 > 100 hr at 120°C (248 °F)

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL. 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site: www.motul.fr

07/09