



Scooter Expert 2T

Lubricant for 2 Stroke Scooter engines

Technosynthese® – Anti-Smoke

TYPE OF USE

All scooters daily used in city/town conditions.
Suitable for 2 Stroke engines, direct injection or conventional carburetor.
Can be used with oil injection systems or in premix.
Suitable for all type of gasoline fuels, leaded or unleaded, biofuels.
Compatible with catalytic converters.

PERFORMANCES

STANDARDS API TC
 ISO-L-EGC

SPECIFICATIONS JASO FD under N° 033MOT071

Technosynthese® engine oil developed for scooter 2 Stroke engines running at high rpm.
Reinforced with synthetic base stocks for outstanding oil film resistance and anti-wear protection.
Avoid deposits and ensures engine cleanliness at all levels: combustion chamber, spark plug, piston top, ring grooves, exhaust port, exhaust pipe...etc.

RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.
To be adjusted according to your own use.

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D1298	0.857
Viscosity at 40°C (104°F)	ASTM D445	65.2 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	9.8 mm ² /s
Viscosity Index	ASTM D2270	133
Flash point	ASTM D92	144°C / 291.2°F
TBN	ASTM D2896	0.97 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: www.motul.com

01/17