

# SPECTRO LUBRICANT TECHNICAL DATA

## Heavy Duty DOT 5 Brake Fluid



### Description

Heavy Duty Silicone DOT 5 is the ideal brake fluid for all Harley® motorcycles requiring a DOT 5 fluid since it is designed to surpass the performance levels of all DOT 5 requirements.

Meets all known OEM warranty requirements.

### Application

Heavy Duty DOT 5 should be used according to the manufacturer's recommended change intervals and directions. No special steps need to be taken when switching to this fluid. DO NOT use where DOT 5.1 and DOT 4 fluids are recommended.

### Typical Inspections

Equilibrium reflux boiling point	260 °C
Humidified equilibrium reflux boiling point	260 °C
Viscosity 40° C cSt	120
Viscosity 100° C cSt	7

Code	Description	Weight
I.GABF	12/355 Liter Bottles	10 Lbs.

- SURPASSES DOT 5 SPECIFICATIONS.
- DESIGNED FOR AMERICAN MOTORCYCLE BRAKING SYSTEMS.
- MEETS OEM FILL REQUIREMENTS, DESIGNED FOR ALL HARLEY BRAKE SYSTEMS CALLING FOR DOT 5 FLUID.
- NON-HYGROSCOPIC, WILL NOT ABSORB WATER.
- WILL NOT HARM PAINTED SURFACES.

SPECTRO OILS OF AMERICA  
993 Federal Rd., Brookfield, CT 06804  
203-775-1291 Fax 203-775-8720  
[www.spectro-oils.com](http://www.spectro-oils.com)

